



## Features & Benefits

- Leading edge optical and digital sensors provide high accuracy and long life
- Drift free readings without further calibration
- Helping companies achieve WELL® and RESET® compliance
- Built in USB port for easy configuration
- Ultimate wireless connectivity through LoRaWAN
- Simple integration with BACnet and Modbus through gateway

## Technical Overview

Our Indoor Air Quality Monitor is a precision instrument which accurately measures up to 9 key environmental parameters including Temperature, Relative humidity, Light level, Particle Matter (PM1, PM 2.5, PM4 & PM10), Sound Level, Volatile organic compounds, Carbon Dioxide, Barometric Pressure. Up to two additional gas sensors may be fitted; one of which must be ozone if two sensors are required. Ammonia, Ozone, Formaldehyde, Carbon Monoxide, Nitrogen Dioxide, Hydrogen Sulphide, Sulphur Dioxide and Oxygen.

## Technical Specification

<b>Radio output type</b>	LoRaWAN
<b>Frequency Range</b>	863-870MHz, 902-928MHz
<b>Security</b>	AES 128 encryption
<b>Power Supply</b>	4 x AA sized 3.6V Lithium Thionyl Chloride. LS14500 Or Externally powered, 12-24VDC Or via PoE splitter Depending on sensor options
<b>VOC's</b>	IAQ Index 0 to 500 (see below) TVOC level (ppm) Variability ±15% (typical) Response time (33-63%) 1 s
<b>Barometric Pressure</b>	0.12hPa (equivalent to ±1m in altitude) Range (with full accuracy): 300 ÷ 1100hPa Resolution: 0.18Pa
<b>Particulate matter</b>	PM0.5, PM1, PM2.5, PM4 & PM10 Sensing method: Laser-based light scattering particle sensing Concentration range: 0-1000µg/m <sup>3</sup> Accuracy: PM1, PM2.5 0µg/m <sup>3</sup> to 100µg/m <sup>3</sup> ± 5µg/m <sup>3</sup> +5% m.v. 100µg/m <sup>3</sup> to 1000µg/m <sup>3</sup> ± 10% m.v. PM4, PM10 0µg/m <sup>3</sup> to 100µg/m <sup>3</sup> ± 25µg/m <sup>3</sup> 100µg/m <sup>3</sup> to 1000µg/m <sup>3</sup> ± 25% Response Time: < 6s (t90) Sensor life expectancy: > 3 years

<b>CO2</b>	Sensing method: Optical. Non-dispersive infrared (NDIR) Accuracy: $\pm(30, +3\%)$ ppm. (typ.) Range: 0-5000ppm. Extended range 1-10,000ppm. Response time: 3min Sensor life expectancy <15years
<b>Operating Humidity</b>	0 – 95%RH, Non-Condensing
<b>Operating Temperature</b>	0 – 40°C
<b>Output range humidity</b>	Accuracy: $\pm 2\%$ (typical) Repeatability: $\pm 0.1\%$ Response time: 15s
<b>Output range temperature</b>	Accuracy: $\pm 0.2^\circ\text{C}$ (typical) Repeatability: $\pm 0.1^\circ\text{C}$ Conversion time: 6.35ms
<b>Housing Material</b>	ABS
<b>Dimensions</b>	168mm Diameter x 47mm
<b>Compliance</b>	Pre-certified radio regulatory approvals: 868 & 915 MHz spectrum CE, FCC, RoHS. Particle matter MCERTS Certified. CO2IWBI WELL v2 Compliant
<b>Country of origin</b>	UK

## Related Product Codes

<b>RF-LW-TIAQ</b>	Indoor Air Quality Monitor. Temperature, Relative Humidity, VOC's, Barometric Pressure. Particulate Matter - PM 1, 2.5, 4, 10. Carbon Dioxide
<b>RF-LW-TIAQ-CO2</b>	Indoor Air Quality Monitor with ultrafine particle sensor. Temperature, Relative Humidity, VOC's, Barometric Pressure. Particulate Matter - PM 0.1, 0.3, 0.5, 1, 2.5, 5, 10. Carbon Dioxide
<b>RF-LW-TIAQ-CO2-SND</b>	Indoor Air Quality Monitor with ultrafine particle sensor. Temperature, Relative Humidity, VOC's, Barometric Pressure. Particulate Matter - PM 0.1, 0.3, 0.5, 1, 2.5, 5, 10. Carbon Dioxide. Sound
<b>RF-LW-TIAQ-SND</b>	Indoor Air Quality Monitor. Temperature, Relative Humidity, VOC's, Barometric Pressure. Particulate Matter - PM 1, 2.5, 4, 10. Carbon Dioxide. Sound
<b>RF-LW-TIAQ-VAPE</b>	Indoor Air Quality Monitor with vape/cigarette smoke detection function and ultrafine particles. Temperature, Relative Humidity, VOC's, Barometric Pressure. Particulate Matter - PM 0.1, 0.3, 0.5, 1, 2.5, 5, 10. Carbon Dioxide.
<b>RF-LW-TIAQ-VAPE-SND</b>	Indoor Air Quality Monitor with vape/cigarette smoke detection function and ultrafine particles. Temperature, Relative Humidity, VOC's, Barometric Pressure. Particulate Matter - PM 0.1, 0.3, 0.5, 1, 2.5, 5, 10. Carbon Dioxide. Sound